# moooi

# Non Random

#### **BERTJAN POT**



Old ladies call them neatly coiled balls of yarn, Kids talk about soap bubbles hanging from lightbulbs. Some say they are there to light up Arabian nights, Moooi says they're Non Random Lights.

## Detailing



Non Random does not shine a random light: the production of its shape is, unlike the Random Light, completely mechanically pre-programmed.

### Colours





Black

White

### Non Random / Non Random D48

#### **Dimensions**

48cm | 18.9"





#### Product

width  $48 \text{cm} \mid 18.9$ "
Height  $54 \text{cm} \mid 21.3$ "
DEPTH  $48 \text{cm} \mid 18.9$ "
DIAMETER  $48 \text{cm} \mid 18.9$ "
WEIGHT NETTO  $1.5 \text{kg} \mid 3.31 \text{lbs}$ 

### **Packaging**

width  $55 \text{cm} \mid 21.7$ "
Height  $63 \text{cm} \mid 24.8$ "
Cubage  $0.19 \text{m}^3 \mid 6.73 \text{ft}^3$ Length  $55 \text{cm} \mid 21.7$ "
Weight  $3.7 \text{kg} \mid 8.16 \text{lbs}$ 

#### Technical CCC

#### MATERIAL

E27

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

A++ to E Yes

LIGHTSOURCE TYPE NUMBER OF LIGHTSOURCES

Incandescent

SHAPE INPUT VOLTAGE
Globe 220-240V

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

LAMPHOLDER RECOMMENDED LIGHTSOURCE

CABLE COLOUR

Black

CABLE LENGTH CANO

400cm | 157.5"; 1000cm | 393.7" Pebble, Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION DIMMING & LIGHTING CONTROL

All directions Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

#### Technical CE

#### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

**ENERGY LABEL** 

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE Globe

FREQUENCY 50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

- 1

INPUT VOLTAGE

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

**CABLE COLOUR** 

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

**DIMMING & LIGHTING CONTROL** 

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical UL

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

Globe

SHAPE

FREQUENCY 50/60

LAMPHOLDER

E26

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

......

INPUT VOLTAGE

MAX POWER CONSUMPTION

60W

**CABLE COLOUR** 

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



## Non Random / Non Random D71

**Dimensions** 

71cm | 28"



/0cm | 2/.6

Product

Packaging

 $\begin{array}{lll} \mbox{width } 71\mbox{cm} \, | \, 28" & \mbox{width } 75\mbox{cm} \, | \, 29.5" \\ \mbox{height } 70\mbox{cm} \, | \, 27.6" & \mbox{height } 82\mbox{cm} \, | \, 32.3" \\ \mbox{depth } 71\mbox{cm} \, | \, 28" & \mbox{cubage } 0.46\mbox{m}^3 \, | \, 16.29\mbox{ft}^3 \end{array}$ 

**DIAMETER** 71cm | 28" **LENGTH** 75cm | 29.5"

**wеіднт Nетто** 1.5kg | 3.31lbs **wеіднт** 6kg | 13.23lbs

#### Technical CCC

#### MATERIAL

E27

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL INSTALLATION REQUIRED

A++ to E Yes

LIGHTSOURCE TYPE NUMBER OF LIGHTSOURCES

Incandescent

SHAPE INPUT VOLTAGE
Globe 220-240V

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

LAMPHOLDER RECOMMENDED LIGHTSOURCE

CABLE COLOUR

Black

CABLE LENGTH CANOPY

400cm | 157.5"; 1000cm | 393.7" Pebble, Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION DIMMING & LIGHTING CONTROL

All directions Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

#### Technical CE

#### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE Globe

FREQUENCY 50/60

LAMPHOLDER

E27

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHT DIRECTION

All directions

**INSTALLATION REQUIRED** 

Yes

NUMBER OF LIGHTSOURCES

- 1

INPUT VOLTAGE

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

**CABLE COLOUR** 

Black

CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

 $\epsilon$ 

Technical UL

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL INSTALLATION REQUIRED

A++ to E

LIGHTSOURCE TYPE NUMBER OF LIGHTSOURCES

Incandescent

SHAPE INPUT VOLTAGE
Globe 110-130V

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

LAMPHOLDER CABLE COLOUR

E26 Black

CABLE LENGTH CANOPY

400cm | 157.5"; 1000cm | 393.7" Pebble II Black, ABS, Pebble, Pebble II White, ABS

LIGHT DIRECTION DIMMING & LIGHTING CONTROL

All directions Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

CULUSTED

## Dimming & Lighting Control

## Mains dimmable with compatible light source

Compatible models: Non Random D48 CE, Non Random D48 UL, Non Random D71 CE, Non Random D71 UL