moooi

The Party Wall Lamp

KRANEN/GILLE



The Party' is inspired by a clan of strong, captivating personalities. Their casted ceramic faces bring to light our fascination with secrets, family dynamics and intrigue. If seen together, as a splendid party, they brighten up the stage with their cool playfulness. Yet behind the lamps' composed façades a mischievous side seeps through and touches our imagination.

Detailing



The lamps share the same basic tactile feel, a subtle roughness given by the granular ceramic finish, but are distinguished by their individual style.

Colours



Grey

The Party Wall Lamp / Bert

Dimensions

16cm | 6.3"

 \Box

| 1 cm | 4.3" | 2cm | | |

Product

WIDTH 16cm | 6.3" **HEIGHT** 22cm | 8.7" **DEPTH** 11cm | 4.3"

WEIGHT NETTO 0.5kg | 1.1lbs

Packaging

width $31.5 \, \text{cm} \mid 12.4"$ Height $31.5 \, \text{cm} \mid 12.4"$ Cubage $0.02 \, \text{m}^3 \mid 0.72 \, \text{ft}^3$ Length $20.5 \, \text{cm} \mid 8.1"$

WEIGHT 3kg | 6.61lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE 220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

77 Im

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 ϵ

Technical UL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

В

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 lm

The Party Wall Lamp / Coco


Dimensions

18cm | 7.1"









Product

WIDTH 18cm | 7.1" **HEIGHT** 22cm | 8.7"

DEPTH 11cm | 4.3"

wеіднт nетто 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"

неіднт 31.5cm | 12.4"

CUBAGE $0.02\text{m}^3 \mid 0.72\text{ft}^3$

LENGTH 20.5cm | 8.1"

WEIGHT 3kg | 6.61lbs

Technical CE

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

В

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 ϵ

Technical UL

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B Yes

LIGHTSOURCE TYPE LIGHTSOURCE INCLUDED

LED Yes

NUMBER OF LIGHTSOURCES INPUT VOLTAGE
1 110-120V

FREQUENCY MAX POWER CONSUMPTION

50/60 6W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHBlack15cm | 5.9"

COLOUR TEMPERATURE CRI

LIGHT DIRECTION

2700 K

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

INSTALLATION REQUIRED

77 Im

85

77 Im

DIMMING & LIGHTING CONTROL


Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.




The Party Wall Lamp / Glenn

Dimensions







Product

width 17cm | 6.7" неіднт 22cm | 8.7" рертн 10cm | 3.9" weight netto 0.5kg | 1.1lbs Packaging

width $31.5 \text{cm} \mid 12.4"$ Height $31.5 \text{cm} \mid 12.4"$ Cubage $0.02 \text{m}^3 \mid 0.72 \text{ft}^3$ Length $20.5 \text{cm} \mid 8.1"$ Weight $3 \text{kg} \mid 6.61 \text{lbs}$

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

LIGHTSOURCE TYPE

LED

В

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE 220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

77 Im

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL INSTALLATION REQUIRED

B Yes

LIGHTSOURCE TYPE LIGHTSOURCE INCLUDED

LED

NUMBER OF LIGHTSOURCES1

110-120V

FREQUENCY MAX POWER CONSUMPTION

50/60 6W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHBlack15cm | 5.9"

COLOUR TEMPERATURECRI2700 K85

LIGHT DIRECTION LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



The Party Wall Lamp / Ted

Dimensions

16cm | 6.3"

10cm | 3.9" 22cm | 8.9"

Product

WIDTH 16cm | 6.3" **HEIGHT** 22cm | 8.7" **DEPTH** 10cm | 3.9"

WEIGHT NETTO 0.5kg | 1.1lbs

Packaging

width $31.5 \, \text{cm} \mid 12.4"$ Height $31.5 \, \text{cm} \mid 12.4"$ Cubage $0.02 \, \text{m}^3 \mid 0.72 \, \text{ft}^3$ Length $20.5 \, \text{cm} \mid 8.1"$

weight 3kg | 6.61lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

В

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE 220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 ϵ

Technical UL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

В

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 Im

The Party Wall Lamp / Mayor


Dimensions

17cm | 6.7"









Product

WIDTH 17cm | 6.7" **HEIGHT** 22cm | 8.7"

DEPTH 10cm | 3.9"

weight netto 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"

неіснт 31.5ст | 12.4"

CUBAGE $0.02\text{m}^3 \mid 0.72\text{ft}^3$

LENGTH 20.5cm | 8.1"

WEIGHT 3kg | 6.61lbs

Technical CE

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

В

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

 ϵ

Technical UL

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B Yes

LIGHTSOURCE TYPE LIGHTSOURCE INCLUDED

LED Yes

NUMBER OF LIGHTSOURCES INPUT VOLTAGE
1 110-120V

FREQUENCY MAX POWER CONSUMPTION

50/60 6W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHBlack15cm | 5.9"

COLOUR TEMPERATURE CRI

LIGHT DIRECTION

2700 K

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI 85

LIGHT OUTPUT

INSTALLATION REQUIRED

77 Im

85

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains, Trailing edge, Reverse phase

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Bert CE, Bert UL, Coco CE, Coco UL, Glenn CE, Glenn UL, Ted CE, Ted UL, Mayor CE, Mayor UL