

m o o o i

Drape Light

JAMIE WOLFOND, 2024



Temporary unavailable. The Drape Light by Jamie Wolfond uses its geometric structure with a 3D-knitted polyester shade to create an essential, deliberate, and warm atmosphere. Shaped by gravity, the shade drapes over two minimalistic glass LED tube lights. This versatile and thoughtful light comes in two sizes and is perfect for every space.

Detailing



Shaped by gravity, the 3D-knitted polyester fabric rests on a minimal frame of two glass tubes encapsulating LED lights.


Colours

Drape Light


Drape Light / 118

Dimensions

118cm | 46,5"



78cm | 30,7"



91cm | 35,8"

Product

WIDTH 118cm | 46.5"

HEIGHT 91cm | 35.8"

DEPTH 78cm | 30.7"

WEIGHT NETTO 3.6kg | 7.94lbs

Packaging

WIDTH 25cm | 9.8"

HEIGHT 21cm | 8.3"

CUBAGE 0.07m³ | 2.43ft³

LENGTH 131cm | 51.6"

WEIGHT 12kg | 26.46lbs

Technical UL / CE

MATERIAL

360° LED lighting in glass tubes with aluminum details, draped 3D-knitted PL fabric

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

3

SHAPE

Abstract

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

50W

LIFETIME

50000 hours

CABLE COLOUR

RAL 9016 (white)

CABLE LENGTH

250cm | 98.4"

SWITCH

No

CANOPY

Pebble III in matching color

CHROM X

0.4588

CHROM Y

0.414

COLOUR TEMPERATURE

2740 K (max)

CRI

81

LIGHT DIRECTION

All directions

LIGHT OUTPUT

3850 lm

R9

0

DIMMING & LIGHTING CONTROL

Wireless Wall Switch (dimmer), DALI dt6, Smart Home Integration (Zigbee), Mains / ELV dimming is not possible, Smart Home Integration (Matter)

See last page for more information about the dimming possibilities.



Energy Label information

LIGHTING TECHNOLOGY USED

LED

DIMMABLE

Yes

ENERGY CONSUMPTION IN ON-MODE (KWH/1000 H)

50 kWh

ENERGY EFFICIENCY CLASS

F

USEFUL LUMINOUS FLUX (ΦUSE)

3850 lm

CORRELATED COLOUR TEMPERATURE

2740 K (max)

ON-MODE POWER (PON)

50W

LIFETIME

50000 hours

COLOUR RENDERING INDEX, ROUNDED TO THE NEAREST INTEGER, OR THE RANGE OF CRI-VALUES THAT CAN BE SET

81


R9 COLOUR RENDERING INDEX VALUE

0

Drape Light / 78

Dimensions

78cm | 30,7"



Product

WIDTH 78cm | 30.7"

HEIGHT 91cm | 35.8"

DEPTH 78cm | 30.7"

WEIGHT NETTO 2.8kg | 6.17lbs

Packaging

WIDTH 25cm | 9.8"

HEIGHT 21cm | 8.3"

CUBAGE 0.06m³ | 2.06ft³

LENGTH 111cm | 43.7"

WEIGHT 10kg | 22.05lbs

Technical UL / CE

MATERIAL

360° LED lighting in glass tubes with aluminum details, draped 3D-knitted PL fabric

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

2

SHAPE

Abstract

INPUT VOLTAGE

120-250V

FREQUENCY

50/60

MAX POWER CONSUMPTION

30W

LIFETIME

50000 hours

CABLE COLOUR

RAL 9016 (white)

CABLE LENGTH

250cm | 98.4"

SWITCH

No

CANOPY

Pebble III in matching color

CHROM X

0.4585

CHROM Y

0.413

COLOUR TEMPERATURE

2740 K (max)

CRI

81

LIGHT DIRECTION

All directions

LIGHT OUTPUT

2150 lm

R9

1

DIMMING & LIGHTING CONTROL

Wireless Wall Switch (dimmer), DALI dt6, Smart Home Integration (Zigbee), Mains / ELV dimming is not possible, Smart Home Integration (Matter)

See last page for more information about the dimming possibilities.



Energy Label information
LIGHTING TECHNOLOGY USED

LED

DIMMABLE

Yes

ENERGY CONSUMPTION IN ON-MODE (KWH/1000 H)

30 kWh

ENERGY EFFICIENCY CLASS

F

USEFUL LUMINOUS FLUX (ΦUSE)

2150 lm

CORRELATED COLOUR TEMPERATURE

2740 K (max)

ON-MODE POWER (PON)

30W

LIFETIME

50000 hours

**COLOUR RENDERING INDEX, ROUNDED TO THE NEAREST INTEGER, OR
THE RANGE OF CRI-VALUES THAT CAN BE SET**

81

R9 COLOUR RENDERING INDEX VALUE

1

Dimming & Lighting Control

Wireless Wall Switch (dimmer)

With our Wireless Wall Switch, you'll have full control over your Moooi lighting design with one touch. Our Wireless Wall Switch comprises two components, a wall switch and radio device to put in the canopy of your Moooi lighting design. The Wall Switch can also be integrated in existing System 55 (i.e. Gira and Jung) or Decora style wall switches. Once the radio device is installed you will also have the possibility to control your light fixture with the Casambi App available in the Google Play and Apple app store. Within moments you can enjoy full and fluent dimming, all the way to dark.

Compatible models: 118 CCC, 118 UL, 118 CE, 78 CCC, 78 UL, 78 CE

DALI dt6

The luminaire is dimmable by integrating it into a DALI network. This is an universal and professional standard in home automation systems with endless control possibilities and ease. We advise to hire a professional to integrate the luminaire into your DALI network.

Compatible models: 118 CCC, 118 UL, 118 CE, 78 CCC, 78 UL, 78 CE

Smart Home Integration (Zigbee)

By adding a Zigbee converter this light fixture can seamlessly integrate into a Zigbee 3.0-based smart home network, such as Philips Hue, Amazon Alexa, Google Home, Ikea Tradfri and Homey. This integration allows for wireless control and compatibility with other smart home systems, without the need to change your home's wiring. To enable this, simply add a Zigbee converter to your luminaire. We recommend the Sunricher Zigbee to Dali Converter for its reliability and compatibility with the US 110 voltage or the Osram 4062172044776 Zigbee 3.0 DALI Converter LI for 210-220V Please note that this converter is sold by third-party vendors and not directly by Moooi and this should be installed by a professional electrician.

Compatible models: 118 CCC, 118 UL, 118 CE, 78 CCC, 78 UL, 78 CE

Mains / ELV dimming is not possible

Mains and/or ELV dimming is not possible. The wireless wall switch is advised for dimming in this case.

Compatible models: 118 CCC, 118 UL, 118 CE, 78 CCC, 78 UL, 78 CE

Smart Home Integration (Matter)

Using the Matter Dali Bridge / Converter this Light can seamlessly integrate in your Matter Smart Home system

like Apple Home, Google Home, Home Assistant, Amazon Alexa, Samsung SmartThings and Homey. We recommend the M2D Bridge Converter for its reliability and compatibility. Please note that this converter is sold by third-party vendors and not directly by Moooli and this should be installed by a professional electrician.

Compatible models: 118 CCC, 118 UL, 118 CE, 78 CCC, 78 UL, 78 CE
