

## NR2

BERTJAN POT




NR2 by Bertjan Pot is an elegant and bright bubble of white or black thread. The lattice pattern creates a fine web that shines and glimmers in the light. The fine web is oval-shaped and bears the signature style of Bertjan Pot; designs created from an experiment with different materials. The integrated LED lamp in NR2 subtly diffuses a soft and magical glow around the room. NR2 is available in two different colours and sizes.

### *Detailing*




NR2's lattice patterned web of clean lines falls into place in any modern interior and brings an element of calmness in a maximalist's home.

### *Colours*




Just Black



White

# NR2 / Large

## Dimensions



## Product

**WIDTH** 75cm | 29.5"  
**HEIGHT** 53cm | 20.9"  
**DEPTH** 75cm | 29.5"  
**DIAMETER** 75cm | 29.5"  
**WEIGHT NETTO** 1.2kg | 2.65lbs

## Packaging

**WIDTH** 78cm | 30.7"  
**HEIGHT** 69cm | 27.2"  
**CUBAGE** 0.42m<sup>3</sup> | 14.82ft<sup>3</sup>  
**LENGTH** 78cm | 30.7"  
**WEIGHT** 8kg | 17.64lbs

## Technical CE

**MATERIAL**  
Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

**ENERGY LABEL**  
B

**LIGHTSOURCE TYPE**  
LED

**NUMBER OF LIGHTSOURCES**  
1

**INPUT VOLTAGE**  
120-277V

**MAX POWER CONSUMPTION**  
26W

**LIFETIME**  
50000 hours

**CABLE LENGTH**  
400cm | 157.5"

**CHROM X**  
0.48

**COLOUR TEMPERATURE**  
2468 K (max)

**LIGHT DIRECTION**  
All directions

**INSTALLATION REQUIRED**  
Yes

**LIGHTSOURCE INCLUDED**  
Yes

**SHAPE**  
Oval

**FREQUENCY**  
50/60

**LAMPHOLDER**  
LED (Solid state)

**CABLE COLOUR**  
Black, White

**CANOPY**  
Pebble II Black, ABS, Pebble II White, ABS

**CHROM Y**  
0.41

**CRI**  
81

**LIGHT OUTPUT**  
1047 lm

#### DIMMING & LIGHTING CONTROL

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

*See last page for more information about the dimming possibilities.*



---

#### Technical UL

#### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

#### ENERGY LABEL

B

#### INSTALLATION REQUIRED

Yes

#### LIGHTSOURCE TYPE

LED

#### LIGHTSOURCE INCLUDED

Yes

#### NUMBER OF LIGHTSOURCES

1

#### SHAPE

Oval

#### INPUT VOLTAGE

120V

#### FREQUENCY

60

#### MAX POWER CONSUMPTION

30W

#### LAMPHOLDER

LED (Solid state)

#### LIFETIME

50000 hours

#### CABLE COLOUR

Black, White

#### CABLE LENGTH

400cm | 157.5"

#### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

#### CHROM X

0.48

#### CHROM Y

0.41

#### COLOUR TEMPERATURE

2468 K (max)

#### CRI

81

#### LIGHT DIRECTION

All directions

#### LIGHT OUTPUT

1047 lm

#### DIMMING & LIGHTING CONTROL

Mains and/or 1-10V dimmable (trailing edge / reverse phase)


*See last page for more information about the dimming possibilities.*



# NR2 / Medium

## Dimensions

55cm | 21.7"



## Product

**WIDTH** 55cm | 21.7"  
**HEIGHT** 40cm | 15.7"  
**DEPTH** 55cm | 21.7"  
**DIAMETER** 55cm | 21.7"  
**WEIGHT NETTO** 0.9kg | 1.98lbs

## Packaging

**WIDTH** 57cm | 22.4"  
**HEIGHT** 52cm | 20.5"  
**CUBAGE** 0.17m<sup>3</sup> | 5.97ft<sup>3</sup>  
**LENGTH** 57cm | 22.4"  
**WEIGHT** 3.7kg | 8.16lbs

## Technical CE

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

G

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

208-277V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

12W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black, White

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### COLOUR TEMPERATURE

2596 K (max)

### CRI

82

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

576 lm

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



---

## Technical UL

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

G

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

120V

### FREQUENCY

60

### MAX POWER CONSUMPTION

16W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black, White

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### COLOUR TEMPERATURE

2700 K (max)

### CRI

82

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

450 lm

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

*See last page for more information about the dimming possibilities.*



## *Dimming & Lighting Control*

### *Mains and/or 1-10V dimmable (trailing edge / reverse phase)*

Compatible models: Large CE, Large UL

---

### *Mains, Trailing edge, Reverse phase*

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Medium CE, Medium UL

---