

m o o o i

## Non Random

BERTJAN POT



Old ladies call them neatly coiled balls of yarn, Kids talk about soap bubbles hanging from lightbulbs. Some say they are there to light up Arabian nights, Moooi says they're Non Random Lights.

---


### *Detailing*



Non Random does not shine a random light: the production of its shape is, unlike the Random Light, completely mechanically pre-programmed.

---

### *Colours*



Black

White

# Non Random / Non Random D48

## Dimensions

48cm | 18.9"



## Product

**WIDTH** 48cm | 18.9"

**HEIGHT** 54cm | 21.3"

**DEPTH** 48cm | 18.9"

**DIAMETER** 48cm | 18.9"

**WEIGHT NETTO** 1.5kg | 3.31lbs

## Packaging

**WIDTH** 55cm | 21.7"

**HEIGHT** 63cm | 24.8"

**CUBAGE** 0.19m<sup>3</sup> | 6.73ft<sup>3</sup>

**LENGTH** 55cm | 21.7"

**WEIGHT** 3.7kg | 8.16lbs

---

## Technical CCC

### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

### ENERGY LABEL

A++ to E

### LIGHTSOURCE TYPE

Incandescent

### SHAPE

Globe

### FREQUENCY

50/60

### LAMPHOLDER

E27

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### LIGHT DIRECTION

All directions

### INSTALLATION REQUIRED

Yes

### NUMBER OF LIGHTSOURCES

1

### INPUT VOLTAGE

220-240V

### MAX POWER CONSUMPTION

60W

### RECOMMENDED LIGHTSOURCE

### CABLE COLOUR

Black

### CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

### DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

---

## Technical CE

### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**SHAPE**

Globe

**FREQUENCY**

50/60

**LAMPHOLDER**

E27

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

220-240V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE****CABLE COLOUR**

Black

**CANOPY**

Pebble, Pebble II Black, ABS, Pebble II White, ABS

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*



---

*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**SHAPE**

Globe

**FREQUENCY**

50/60

**LAMPHOLDER**

E26

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

110-130V

**MAX POWER CONSUMPTION**

60W

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source



*See last page for more information about the dimming possibilities.*



# Non Random / Non Random D71

## Dimensions

71cm | 28"



## Product

**WIDTH** 71cm | 28"  
**HEIGHT** 70cm | 27.6"  
**DEPTH** 71cm | 28"  
**DIAMETER** 71cm | 28"  
**WEIGHT NETTO** 1.5kg | 3.31lbs

## Packaging

**WIDTH** 75cm | 29.5"  
**HEIGHT** 82cm | 32.3"  
**CUBAGE** 0.46m<sup>3</sup> | 16.29ft<sup>3</sup>  
**LENGTH** 75cm | 29.5"  
**WEIGHT** 6kg | 13.23lbs

---

## Technical CCC

### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

### ENERGY LABEL

A++ to E

### LIGHTSOURCE TYPE

Incandescent

### SHAPE

Globe

### FREQUENCY

50/60

### LAMPHOLDER

E27

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### LIGHT DIRECTION

All directions

### INSTALLATION REQUIRED

Yes

### NUMBER OF LIGHTSOURCES

1

### INPUT VOLTAGE

220-240V

### MAX POWER CONSUMPTION

60W

### RECOMMENDED LIGHTSOURCE

### CABLE COLOUR

Black

### CANOPY

Pebble, Pebble II Black, ABS, Pebble II White, ABS

### DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

---

## Technical CE

### MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**SHAPE**

Globe

**FREQUENCY**

50/60

**LAMPHOLDER**

E27

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

220-240V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE****CABLE COLOUR**

Black

**CANOPY**

Pebble, Pebble II Black, ABS, Pebble II White, ABS

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.**Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**SHAPE**

Globe

**FREQUENCY**

50/60

**LAMPHOLDER**

E26

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**LIGHT DIRECTION**

All directions

**INSTALLATION REQUIRED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

110-130V

**MAX POWER CONSUMPTION**

60W

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble, Pebble II White, ABS

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

## *Dimming & Lighting Control*

### *Mains dimmable with compatible light source*

Compatible models: Non Random D48 CE, Non Random D48 UL, Non Random D71 CE, Non Random D71 UL

---